

Novatech

500 Series Patio Doors






The 540 and 550 doors offer **exceptional energy efficiency** that meets the **Energy Star** standard while the Element door features superior durability and an outstanding finish thanks to its aluminum cladding. Their wide choice of sizes and configurations are suitable for any type of building.




The **540** door: Simple and bright With a quality finish, the 540 patio door adapts to any type of project. Thanks to its large glazed surface, you can make the most of the view while filling your house with natural light.



The **550** door: Quality assured

With its clean profile and elegant handle, the 550 door offers a modern look that blends in with your decor. Its many options, including integrated blinds, will allow you to customize your door to perfectly match your environment. This high-quality door is a sure value.



Add color with the **ELEMENT** door

The advantages of a patio door with **aluminum cladding** are undeniable: enhanced look, strength and durability. With its 5 trendy colors, Element allows you to personalize your door. Let your creativity run free to create the incredible decor you dream of.

Five colors of exterior aluminium cladding at no additional cost! Standard white PVC interior.











Clear anodized










Features	540	550	ELEMENT		
Frame					
Aluminum clad frame			✓		
Frame depth	5 3/4", 7 1/4", 9 3/4"	5 ¾" to 11 ¾"	5½" to 11¾"		
Quick draining sill sloped at 9°	~	✓	✓		
Pocket Covers	PVC inside — Option	PVC inside and outside — Option	Aluminium outside — Included PVC inside — Option		
Aluminum sill cover	Option	Option			
Give your 550 door a superior look and finish with these two options.					
Sash					
Aluminum clad sash			*		
45° fusion welded corners and interior glazing stops		✓	Y		
Steel reinforcements in the vertical stiles	*	✓	*		
Exterior Colors					
White	✓	✓			
Black (Painted)	Option	Option			
Five standard colors of aluminum cladding			*		
Custom colors		Option	Option		
Insulated Glass					
Tempered Low E glass with low-conductive spacer	~	✓	*		
Hardware					
Look contemporary style handle		✓	*		
View contemporary style handle		Option	Option		
9600 Handle	✓				

Options



Colors



More than 100 colours available. Custom colours on demand. (550, Element)

Black (Option)

Decorative Options

(Only available with 550 and Element doors.)



Dividers Rectangular 2", 1×3 or 1×4



GridsRectangular or georgian %", 3 × 6



Oil Rubbed Bronze (Paint)

Satin Nickel

Hanging Grids Rectangular or georgian 5%" ou 1", 3×1

Integrated blinds

(Only available with 550 and Element doors.)



Integrated blinds are a great way to let light in during the day while ensuring absolute privacy at any moment. Easy to operate with two discreet buttons. Because the blinds are between the glass, they are virtually maintenance free.





White Satin gray

Security **Options**



Double-point mortise lock (Shown with Look handle) (550, Element)



Three-position foot lock (Only available in white) (550, Element)



Security bar (Only available in white)

Other **Options**

Configuration	540	550	Element
Transoms		•	•
Sidelites		•	•
Aluminum sill cover	•	•	Standard
Interior PVC jamb pocket cover	•	•	
Exterior PVC jamb pocket cover		•	
Exterior Aluminum jamb pocket cover			Standard
Reinforced screen		•	•
Glass options	540	550	Element
Low E glazing with argon	•	•	•
Triple glazing		•	•
Tinted glass (Bronze or gray)		•	•

Installation options	540	550	Element
Wood extension on 3 or 4 sides with interior PVC cladding	•	•	•
PVC Brick mould		•	•
Aluminum sill extension		•	•
Drywall return		•	•
Nailing fin		•	•

Performance

Harmonized standards

	540	550	ELEMENT
Air leakage resistance	A3	A3	A3
Water penetration resistance	360 Pa	400 Pa — 440 Pa with Sill Tower Riser (Option)	400 Pa
Uniform load structural test	DP-30	DP-40	DP-45
Global	PG-R30	PG-R40	SD-R45
Laboratory tested	Reference 95½" × 81"	Reference 71½" × 81"	Reference 71½" × 81"

AAMA / WDMA / CSA101 / I.S.2 / A440-17 (NAFS 2017) & CSA A440S1:19

AAMA / WDMA / CSA101 / I.S.2 / A440-11 (NAFS 2011), CSA A440S1-09 & CSA A440S1-17

	Insulated Glass		540		550			ELEMENT		
			ER U Value		ER U Value		ER	ER U Value		
Standard	Double glazed — Low E on face 3	34	1.70 EN	IERGY STAR	34	1.70	ENERGY STAR	34	1.76	ENERGY STAR
Option	Triple glazed — Low E on face 5	_	_		38	1.36	ENERGY STAR	40	1.48	ENERGY STAR

Warranty



20-year limited warranty. See the detailed warranty on our website.

The information in this brochure is current as of the date of publication but is subject to change.

